Laboratory Scale Evaluation of Hydra-Tone Graff-Off[™] Coconut Oil-Based Degreaser

by

James R. Nutor and James K. Rose Battelle 505 King Avenue Columbus, Ohio 43201-2693

Contract No. 68-C7-0008 Work Assignment Numbers 2-19

> to Dr. George Moore Project Officer

and Mr. David Ferguson Work Assignment Manager

U.S. Environmental Protection Agency Office of Research and Development National Risk Management Research Laboratory Cincinnati, Ohio 45268

Notice

The information in this document has been funded by the United States Environmental Protection Agency (U.S. EPA) under Work Assignment (WA) Nos. 2-19 of Contract No. 68-C7-0008 to Batelle. It has been subjected to the U.S. EPA's peer and administrative reviews, and has been approved for publication as a U.S. EPA document. Mention of trade names or commercial products does not constitute an endorsement or recommendation for use.

Abstract

This technical and economic assessment evaluated the effectiveness of a biodegradable, coconut oil-based degreaser called Graff-Off[™]. In immersion ("cold") cleaning and rinse tests, Graff-Off[™] was compared to a conventional chlorinated solvent 1,1,1 trichloroethane (TCA) and to an alkaline cleaner Aeroclean DN-30 (DN-30). The cleaning process for Graff-Off[™] and TCA was at room temperature and that of DN-30 was at 71° C. Both alternatives were found to be technically superior to TCA. Both alternative degreasers had lower cleaner costs and allowed a greater surface area to be cleaned per unit volume of degreaser than the TCA. Estimated savings were significant and capital requirements were modest. An economic assessment based on net present value, internal rate of return, and payback period indicated that Graff-Off[™] and the DN-30 alkaline cleaner were extremely attractive alternatives to TCA (TCA assessment was based on immersion "cold" cleaning without vaporization and without TCA recycling).

Contents

	Notice				
			reviations		
Fore	wora	•••••		x	
1.0	Introduction				
	1.1		round		
	1.2		rial Opportunity		
	1.3		tive		
2.0	Cond				
3.0			ations		
4.0		ods and	Materials	4	
	4.1		ystem Definition and Selection		
		4.1.1	Cleaning Process Selection	4	
		4.1.2	Alternate Alkaline Cleaner Selection		
		4.1.3	Solvent Cleaner Selection		
		4.1.4	Cleaning Object Selection		
		4.1.5	Contaminant Selection		
		4.1.6	Pre-Contamination of Degreaser Bath		
	4.2		mental Set-up		
		4.2.1	Materials	4	
		4.2.2	Beaker Test for Bath Exhaustion Determination		
		4.2.3	Panel Contamination	5	
			4.2.3.1 Panel Holding Racks	5	
			4.2.3.2 Panel Labeling	5	
			4.2.3.3 Automated Immersion Unit		
	4.0	Ola:	4.2.3.4 Panel Contamination Process		
	4.3		ng Process		
		4.3.1	Cleaning Bath		
		4.3.2	Rinse Tanks		
		4.3.3 4.3.4	Cleaning System Accessories		
		4.3.4	Cleaning Operation		
			4.3.4.1 Preparation for Contaminated Panel Cleaning		
			4.3.4.2 Panel Cleaning Procedure		
	4.4	Dorfor	mance Measurements		
	4.4	4.4.1	Panel Sampling		
		4.4.2	Bath Exhaustion Indicators		
		7.7.2	4.4.2.1 Water-Break Test		
			4.4.2.2 Weight Change Test		
			4.4.2.3 Non-Volatile Residue Measurements (NVR)	10 10	
			4.4.2.4 Fourier Transform Infrared Spectroscopy (FTIR)		
		4.4.3	Rinse Bath Monitoring		
		4.4.4	Other Observational Methods		
	4.5		mic Assessment		

5.0	Results and Discussion			
	5.1	Load of Jet Engine Oil on Contaminated Panels	12	
	5.2			
		Pre-Contamination Level	12	
	5.3			
	5.4			
	5.5	Cleaning Performance by Other Observations	13	
		5.5.1 Physical Properties of the Cleaners	13	
		5.5.2 Cleaning Process Observations		
		5.5.3 pH and Temperature of Baths		
		5.5.4 Particulates in the Cleaning Baths		
		5.5.5 Panel Corrosion		
	5.6	Rejuvenation of Exhausted Degreaser Baths		
6.0	Ecor	nomic Analysis	16	
	6.1 Assumptions			
		6.1.1 Commercial Job Shop	16	
		6.1.2 Large Shop Operation		
	6.2 Life Cycle Analysis			
		6.2.1 Financial Performance Measure	18	
		6.2.2 Capital Costs		
		6.2.3 Retrofit Cost		
		6.2.4 Capital Replacement		
		6.2.5 Annual Operating Costs		
	6.3	Investment Analysis and Conclusions		
7.0	Refe	rences	24	
8.0		endices		

Figures

Figure 1.	Panel rack.	6
Figure 2.	Automated test panel immersion system.	7
Figure 3.	Cleaner bath with submerged rack and panels	8
Figure 4.	Rinse tanks with rinse water addition nozzles.	g
Figure 5.	Beaker test results compared to actual bath cleaning results	14
Figure 6.	Total surface area cleaned at bath exhaustion	15

Tables

lable 1.	List of Critical and Non-Critical Performance Measurements	9
Table 2.	Summary of Non-Critical Surface Finishing Bath and Rinse Water Analyses	. 10
Table 3.	Results of Beaker Test	. 12
Table 4.	Estimated Degreaser Requirements	. 17
Table 5.	Utility Requirements	. 17
Table 6.	Large-Scale Operations Degreaser Requirements	. 18
Table 7.	Large-Scale Operations Utility Requirements	. 19
Table 8.	Estimated Values Used in the Cost Assessment	. 19
Table 9.	Summary of Investment Criteria	. 20
Table 10.	Estimated Initial Capital Investment	. 20
Table 11.	Retrofit and Training Costs	. 21
Table 12.	Estimated Net Change in Capital Investment	. 21
Table 13.	Estimated Annual Costs	. 22
Table 14.	Investment Assessment	. 23

Acronymns and Abbreviations

ASTM American Society for Testing and Materials

CAA Clean Air Act CFC chlorofluorocarbons COCF Chain of Custody Form

DN-30 Aeroclean DN-30 – an alkaline cleaner

EPA United States Environmental Protection Agency

FTIR Fourier Transform Infrared Spectroscopy

HBFC hydrogen bromine fluorocarbons **HCFC** hydrogen chlorofluorocarbons HTCI Hydra-tone Chemicals, Inc.

IRR internal rate of return NPV net present value

NRMRL National Risk Management Research Laboratory

NVR non-volatile residue PCE perchloroethylene PΕ purchased equipment P2 **Pollution Prevention** QC

quality control

TCA 1,1,1 trichloroethane – a solvent cleaner

TCE trichloroethylene TO technical order

U.S. EPA United States Environmental Protection Agency

VOCs volatile organic compounds

Foreword

The U.S. Environmental Protection Agency is charged by Congress with protecting the Nation's land, air, and water resources. Under a mandate of national environmental laws, the Agency strives to formulate and implement actions leading to a compatible balance between human activities and the ability of natural systems to support and nurture life. To meet this mandate, EPA's research program is providing data and technical support for solving environmental problems today and building a science knowledge base necessary to manage our ecological resources wisely, understand how pollutants affect our health, and prevent or reduce environmental risks in the future.

The National Risk Management Research Laboratory (NRMRL) is the Agency's center for investigation of technological and management approaches for preventing and reducing risks from pollution that threaten human health and the environment. The focus of the Laboratory's research program is on methods and their cost-effectiveness for prevention and control of pollution to air, land, water, and subsurface resources; protection of water quality in public water systems; remediation of contaminated sites, sediments and ground water; prevention and control of indoor air pollution; and restoration of ecosystems. NRMRL collaborates with both public and private sector partners to foster technologies that reduce the cost of compliance and to anticipate emerging problems. NRMRL's research provides solutions to environmental problems by: developing and promoting technologies that protect and improve the environment; advancing scientific and engineering information to support regulatory and policy decisions; and providing the technical support and information transfer to ensure implementation of environmental regulations and strategies at the national, state, and community levels.

This publication has been produced as part of the Laboratory's strategic long-term research plan. It is published and made available by EPA's Office of Research and Development to assist the user community and to link researchers with their clients.

E. Timothy Oppelt, Director National Risk Management Research Laboratory